



## Petroleum & Flammable Liquid Cupboard Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>	<u>Shelves Supplied</u>	<u>Sump Capacity</u>
1200mm	900mm	460mm	2	14 Litres
1200mm	1200mm	460mm	2	16 Litres
<b>(Floor Chest)</b> 610mm	1170mm	460mm	-	20 Litre
<b>(Floor Chest)</b> 510mm	610mm	340mm	-	7 Litres

### Cupboard Construction:

- 1.2mm mild steel, seam-welded carcass construction
- Full length piano hinges
- Rust resisting galvanised shelves
- Integral liquid-tight sump fitted at the bottom of the cupboard
- Door aperture has return bends to eliminate open gaps
- Delivered assembled
- Reaction to Fire Classification EN 13501-1 – documents available
- Supplied with one warning label
- Seven lever safe lock and an anti-pick locking mechanism
- Extra Shelves are available with the Petroleum & Flammable Liquid Cupboard range

### Cupboard Sump Construction:

- Material: 1.2mm Mild Steel
- Fully welded seams
- Sump Integral

### **Cupboard Door Construction:**

- 1.2mm thick steel door with full length welded/riveted continuous hinge, incorporating retaining rail to prevent hinge/door removal.
- Two point espagnolette locking mechanism secures both doors into carcass. Fitted with a 7 lever Lowe & Fletcher 2802 anti-pick safe lock.

### **Carcass & Door Paint Finish:**

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard anti-bacterial compound
- Powder coated with Red RAL 3003

### **Cleaning & Maintenance:**

- Clean paint work periodically with warm soapy water or Foaming cleaner
- Oil hinges and lock sparingly as required with a light oil (3in1 or similar)