



Sizes & Compartments Available

Sizes:

- 1800Hx300Wx300Dmm
- 1800Hx300Wx450Dmm
- 1800Hx380Wx380Dmm
- 1800Hx450Wx450Dmm

Door Compartment Options:

- 1 Compartment
- 2 Compartments
- 3 Compartments
- 4 Compartments
- 5 Compartments
- 6 Compartments

Internal Compartment Sizes:

1800Hx300Wx300Dmm

- 1 Compartment - 1698Hx245Wx275Dmm
- 2 Compartments - 830Hx245Wx275Dmm
- 3 Compartments - 548Hx245Wx275Dmm
- 4 Compartments - 408Hx245Wx275Dmm
- 5 Compartments - 318Hx245Wx275Dmm
- 6 Compartments - 260Hx245Wx275Dmm

1800Hx300Wx450Dmm

- 1 Compartment - 1698Hx245Wx430Dmm
- 2 Compartments - 830Hx245Wx430Dmm
- 3 Compartment - 548Hx245Wx430Dmm
- 4 Compartments - 408Hx245Wx430Dmm
- 5 Compartments - 318Hx245Wx430Dmm
- 6 Compartments - 260Hx245Wx430mm





1800Hx380Wx380Dmm

- 1 Compartment - 1698Hx330Wx360Dmm
- 2 Compartments - 830Hx330Wx360Dmm
- 3 Compartments - 546Hx330Wx360Dmm
- 4 Compartments - 408Hx330Wx360Dmm
- 5 Compartments - 318Hx330Wx360Dmm
- 6 Compartments - 260Hx330Wx360Dmm

1800Hx450Wx450Dmm

- 1 Compartment - 1698Hx395Wx430Dmm
- 2 Compartments - 830Hx395Wx430Dmm
- 3 Compartments - 546Hx395Wx430Dmm
- 4 Compartments - 408Hx395Wx430Dmm
- 5 Compartments - 315Hx395Wx430Dmm
- 6 Compartments - 260Hx395Wx430Dmm



Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180 deg, including our germ guard anti-bacterial compound.

The carcass is powder-coated - Light Grey RAL 7035.

Doors are powder-coated with a choice of Dark Grey RAL 7024, Red RAL 3003, Green RAL 6024, Light Grey RAL 7035, Light Blue RAL 5012, Dark Blue RAL 5017 & Yellow RAL 1018.



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner. Oil hinges and lock sparingly as required with a light oil (3in1 or similar).



Locker Construction

General Construction:

- 0.7mm mild steel, pop riveted carcass construction.
- Rust-resisting galvanised shelves.
- Delivered as a fully assembled unit.
- Pre-drilled carcass for nesting lockers together to complete a run/bank.
- Fitted with standard master cam locks with 2,000 differs.
- Single compartment locker fitted with top shelf and coat hook.
- Two-tier lockers fitted with coat hook in each compartment.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.

Locker Door Construction:

- A door stiffener is spot welded vertically in the centre of the door (except for 6 door units), the door is attached by pop rivets to the right-hand side of the carcass with two 38mm butt hinges and fitted with 10 disc key operated cam lock. Alternatively, swivel latch locks (to accept padlocks supplied by others) can be specified.



Delivery

All sizes and compartment options are manufactured-to-order item and will be on an extended lead-time.



Our live chat satisfaction rating,
based on user feedback